



## C TYPE HOOKS QUESTIONNAIRE

- DATE
- CUSTOMER
- PERSON OF CONTACT
- UNITS
- COIL MAXIMUM WEIGHT  kg.
- MINIMUM INTERIOR DIAMETER ( $\phi A$ )  mm.
- MAXIMUM OUTER DIAMETER ( $\phi B$ )  mm.
- COIL LENGTH (C)  mm.

THINGS TO CONSIDER IN CASE COILS ARE ON A COIL TURNSTYLE:

- COIL TURNSTYLE INTERIOR WIDTH (D)  mm.
- COIL TURNSTYLE MAXIMUM INTERIOR WIDTH (D)  mm.

C TYPE HOOK MUST CARRY PLASTIC PROTECTIONS:  YES  NO

CRANE FEATURES:

- LIFTING ACCELERATION  m/s<sup>2</sup>

HOOK BLOCK DIMENSIONS

F DISTANCE  mm.      G DISTANCE  mm.  
 H DISTANCE  mm.      I DISTANCE  mm.

- HOOK BLOCK MAXIMUM HEIGHT ABOVE THE GROUND (J DISTANCE)  mm.

● WORK FACTOR

<input type="checkbox"/>	<b>Light</b>	Lifting devices occasionally used to the maximum load and often used on very light loads.
<input type="checkbox"/>	<b>Medium</b>	Lifting devices usually used to the maximum load and often used on light loads.
<input type="checkbox"/>	<b>Heavy</b>	Lifting devices often used to the maximum load and usually used on medium loads.
<input type="checkbox"/>	<b>Very Heavy</b>	Lifting devices often used on loads near the maximum load capacity.

● WORK TO PERFORM / OTHER SPECIFICATIONS

